

Valid for	ASFINAG MAUT SERVICE GMBH
-----------	---------------------------

Austrian HGV Tolling System

EETS-DSRC Transaction for Tolling and Enforcement

For information only

(Subject to change without notice)

Document Reference	Version	Status	Security	Date
[EETS-DSRC]	V1.11	released		06.05.2014

Established	Checked	Approved
<i>Name / Dept.:</i> HHA/ MSG-SE	<i>Name / Dept.:</i>	<i>Name / Dept.:</i> MHA/ MSG-GF
<i>Date:</i>	<i>Date:</i>	<i>Date:</i>

Distribution	
---------------------	--

History

Version	Date	Modification	Established	Approved
1.1	21.03.2013	EDS version	HHA	
1.11	06.05.2014	Disclaimer changed (no change of contents), doc. history added	HHA	
1.12	14.07.2014	Version of EN ISO 14906 updated	HHA	MHA

Table of Contents

1	GENERAL	6
1.1	PURPOSE OF THE DOCUMENT.....	6
1.2	EETS TOLLING AND ENFORCEMENT TRANSACTION.....	7
1.3	EETS ENFORCEMENT ONLY TRANSACTION	8
1.4	SECURITY FEATURES.....	8
1.5	DATA SPECIFICATION.....	8
2	EETS TOLLING AND ENFORCEMENT TRANSACTION	9
2.1	DECISION FLOW	9
2.2	BIT LEVEL SPECIFICATION	10
3	EETS ENFORCEMENT ONLY TRANSACTION	21
3.1	BIT-LEVEL SPECIFICATION.....	21
4	ANNEX A - REFERENCES	25

Abbreviations and Glossary

Abbreviation, Term	Description
AID	DSRC-Application Entity Identifier
AttrID	Attribute Identifier
AuKey_Iss	(Issuer) Authentication Key
BST	Beacon Service Table
CI	Contract Issuer = Toll Service Provider (TSP) = EETS Provider
DSRC	Dedicated Short Range Communication
EFC	Electronic Fee Collection
EID	Element Identifier
FCS	Frame Check Sequence
HGV	Heavy Goods Vehicle
HMI	Human-Machine Interface
HV	Heavy Vehicle (> 3.5 tons)
IID	Invoker Identifier
KeyRef_CI	Key reference for TSP- (CI-) authenticator key
KeyRef_OP	Key reference for TC- (OP-) authenticator key
L1	Layer 1 of DSRC (Physical Layer)
L2	Layer 2 of DSRC (Data Link Layer)
L7	Layer 7 of DSRC (Application Layer)
LID	Link Identifier
LLC	Logical Link Control
LPN	Licence Plate Number
MAC	Medium Access Control
MMI	Man Machine Interface
OBE	On-Board Equipment
OBU	On-Board Unit
PDU	Protocol Data Unit
RSE	Roadside Equipment

TC	Toll Charger
TSP	Toll Service Provider = Contract Issuer (CI) = EETS Provider
UI	User Interface (= MMI)
VST	Vehicle Service Table

References

All references are listed in Annex A - References of this document. For dated references, subsequent amendments to or revisions of any of these publications apply only when incorporated in it by amendment or revision. For undated references, the latest edition of the referenced publication applies.

1 General

1.1 Purpose of the document

This specification provides the definition for the DSRC transactions used in EETS context according to EN 15509.

This specification applies for post-pay transactions for communication between OBE and roadside tolling equipment and in case of multilane free flow systems for combined tolling and enforcement RSE.

In general, the transaction is based on the “pick what you like” idea, i.e. it is up to the Toll Charger which attribute must be read to allow correct charging. This chapter gives an exemplary definition of the DSRC transactions, between the EETS-OBE and the Road Side Equipment (RSE).

The table below provides an overview of the attributes involved in the data exchanges of DSRC transactions associated with the EETS-OBE.

ATTRIBUTES (EID>0)	AttrID	Tolling & enforcement	Enforcement only
EFC Context Mark	0	X	X
Contract Authenticator	4	*)	*)
VehicleLicencePlateNumber	16	X	X
VehicleClass	17	X	X
VehicleDimensions	18	**)	**)
VehicleAxles	19	X	X
VehicleWeightLimits	20	**)	**)
VehicleSpecificCharacteristics	22	X	X
VehicleAuthenticator	23	*)	*)
EquipmentOBUId	24	X	X
EquipmentStatus	26	X	
PaymentMeans (including PAN)	32	X	X
ReceiptData1	33	X	X
ReceiptData2	34	X	X

*) Attributes 4 and 23 are optional (not foreseen in EN 15509); use is up to the Toll Charger (if supported by OBE).

***) Attributes 18 and 20 are not used in this exemplary description.

1.2 EETS Tolling and enforcement transaction

A tolling and enforcement transaction is performed for the purpose of charging and, if applicable, enforcing the due tolling fee.

The following table shows an example for such a transaction. A dedicated implementation has to be tailored to the toll chargers needs.

Phase	Roadside Equipment		On-board unit	Remarks
<i>Initialisation</i>	INITIALISATION.request (BST)	→		RSE periodically sends BST.
<i>(BST – VST)</i>		←	INITIALISATION.response (VST) <ul style="list-style-type: none"> EFC-ContextMark AC_CR-KeyReference RndOBE 	A newly arrived OBE answers with VST. According to the information in the VST, the RSE decides whether the OBE/Contract is acceptable or not. If not the presentation phase is not started.
<i>Presentation</i>	GET_STAMPED.request AC_CR <ul style="list-style-type: none"> PaymentMeans, including PersonalAccountNumber (RndRSE, KeyRef_CI) GET.request <ul style="list-style-type: none"> EquipmentOBUId ReceiptData1 EquipmentStatus Vehicle data: <ul style="list-style-type: none"> VehicleClass VehicleAxles VehicleSpecificCharacteristics 	→		Read PaymentMeans (including Personal Account Number) and request the OBE to calculate the CI authenticator Read data that serves as a basis for calculating the fee (i.e.vehicleClass, VehicleAxles, VehicleSpecificCharacteristics) and data for diagnostics, auditing and controlling (i.e. Equipment OBE Id, Receipt Data1, EquipmentStatus). The Attribute VehicleLicencePlateNumber is read out in the receipt phase in order to provide a better distribution of data in uplink frames between the presentation and the uplink phases.
		←	GET_STAMPED.response <ul style="list-style-type: none"> Authenticator (Auth_CI) GET.response	OBE responds with the requested data, plus the CI Authenticator computed over Payment Means (including Personal Account Number)
<i>Receipt</i>	GET_STAMPED.request AC_CR <ul style="list-style-type: none"> PaymentMeans, including PersonalAccountNumber (RndRSE, KeyRef_OP) GET.request AC_CR <ul style="list-style-type: none"> Vehicle data: <ul style="list-style-type: none"> VehicleLicencePlateNumber SET.request AC_CR <ul style="list-style-type: none"> ReceiptData1 ReceiptData2 EquipmentStatus SET_MMI.request	→		Read Payment Means (including Personal Account Number) and request the OBE to calculate an authenticator for the Toll Charger. Write new receipt (or entry ticket) to ReceiptData1. Copy old receipt to ReceiptData2 Write new status information and increment transaction counter. Signal the transaction's result via the OBE's HMI: OK, Warning or NOK
		←	GET_STAMPED.response <ul style="list-style-type: none"> Authenticator (Auth_OP) GET.response SET.response SET_MMI.response	
<i>Tracking</i>	ECHO.request	→		Track OBE by exchanging dummy information. The usage of Echo is optional, at the discretion of the RSE, and may be repeated (used e.g. at enforcement equipment in multilane free flow systems).
<i>And</i>		←	ECHO.response	
<i>Closing</i>	EVENT_REPORT.request (Release)	→		RSE closes transaction and releases OBE

1.3 EETS Enforcement only transaction

An enforcement transaction is performed for enforcement purposes only, e.g. used by mobile enforcement equipment.

Phase	Roadside Equipment		On-board unit	Remarks
<i>Initialisation</i>	INITIALISATION.request (BST)	→		
(BST – VST)		←	INITIALISATION.response (VST)	
<i>Presentation 1</i>	GET.request AC_CR <ul style="list-style-type: none"> • EquipmentOBUId • EquipmentStatus (transaction counter) • Vehicle data: <ul style="list-style-type: none"> - VehicleLicencePlateNumber - VehicleClass - VehicleAxles - VehicleSpecificCharacteristics 	→		
		←	GET.response	
<i>Presentation 2</i>	GET.request AC_CR ReceiptData1 ReceiptData2	→		
		←	GET.response	
<i>Closing</i>	EVENT_REPORT.request (Release)	→		

1.4 Security features

The EETS DSRC transaction comprises the following security features:

- **Transaction counter**, increased by the RSE, allowing detection of transaction sequencing anomalies in the central system.
- **Authentication to the EETS Provider (Contract Issuer)**, i.e. challenge-response of PaymentMeans data using the GET_STAMPED function with the CI Key
- **Authentication to the Toll Charger**, i.e. challenge-response of PaymentMeans data using the GET_STAMPED function with the Operator Key
- **Protected access** to the OBE's data, through the implementation of Access Credentials (Security level 1 according to EN 15509).

1.5 Data specification

The data definition (attribute data) is given in the document [EETS-OBE_data].

2 EETS tolling and enforcement transaction

2.1 Decision flow

Each time the RSE receives a VST from an OBE it analyses the attribute EFC-ContextMark and if necessary, the data elements EquipmentClass + ManufacturerID, in order to decide which application to use. If those elements correspond to one of the entries in the RSE's Contract Issuer List the RSE will proceed with the associated application to perform a suitable transaction. In case of an EETS-OBE the Tolling and Enforcement Transaction has to apply.

If the VST contains a list of (more than one) EFC-ContextMark, the first entry that can be matched with an entry in the Contract Issuer List of the RSE will be used.

Access Credentials are used in the further transaction steps if the entry in the Contract Issuer List indicates to use security level 1.

The VST contains an ApplicationContextMark with:

For security level 0 (no AC_CR):	EFC-ContextMark (6 Bytes)
For security level 1 (AC_CR used):	EFC-ContextMark, AC_CR_Keyreference, RndOBU (in total 16 Bytes)

Access Credentials are used in the further transaction steps if the entry in the Contract Issuer List indicates to do so. Note: If AC_CR are not used, the RSE will accept a VST with an ApplicationContextMark of 6 Bytes or of 16 Bytes. In the second case, it will simply ignore the additional 10 Bytes.

The first GET_STAMPED.request is performed with the suitable authenticator key for the service provider authentication as listed in the Contract Issuer List for that EFC-ContextMark.

Note:

The SET_MMI command is used with a container type compliant to the OBE, which can be controlled by an appropriate entry in the Contract Issuer List, preferable the container type according to the last draft version of [EFC-API] (69h) shall be used.

If the PaymentMeans-ExpiryDate is older than RSE current station's date, the OBE shall be handled like an OBE with invalid PaymentMeans (SET_MMI.request: 4 beep code).

Value “0” of PaymentMeans-ExpiryDate means that there is no Expiry Date to be checked.

If the 15th bit of EquipmentStatus is set to 1 the OBE shall be handled as a “blacklisted OBE”, if the Contract Issuer List indicates to do so (SET_MMI.request: 4 beep code).

The second GET_STAMPED.request is performed with the suitable authenticator key for the toll charger authentication as listed in the Contract Issuer List for that EFC-ContextMark.

The RndRSE number is the same for both GET_STAMPED.request.

2.2 Bit level specification

The specification is valid for the complete frame content (excluding the zero-bit insertions) of the data exchanged, including protocol information related to DSRC-L1, -L2 and -L7, in order to ensure unambiguity.

Note:

This bit-level specification has been written with the following constraints: EquipmentOBUID with length 4+1 Byte and VehicleLicencePlateNumber with length 13 Byte (LPN with 10 characters – minimal length). The bit-level changes accordingly, when these attributes have different length (see [EETS-OBE_data]). As the transaction according to EN 15509 is based on the idea to read only attribute data needed for the tolling functionality in the specific tolling context, the following tables are only representing examples.

In the following tables, lines for octets only present or valid for security level 1 (Access credentials) are marked by grey colour and numbered (most left column) by letters (A, B, C,).

2.2.1 Initialization

2.2.1.1 Initialization request (BST)

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Broadcast \$	1111 1111	Link address for broadcast
3	MAC control field	1010 0000	The frame contains a command LPDU
4	LLC control field	0000 0011	UI command
5	Fragmentation header	1xxx x001	No fragmentation. PDU # shall never be set to 0000 ₂ or 0001 ₂ .
6	BST SEQUENCE {	1000	INITIALISATION.request
	OPTION indicator	0	NonmandApplications not present.
7	BeaconId.ManufacturerId INTEGER (0..65535)	000	Manufacturer identifier: 1 (=Kapsch). See [AVI No] Register at www.nen.nl/cen278 for value assignment.
		0000 0000	
8	BeaconId.IndividualId INTEGER (0..134217727)	0000 1	27 bit ID available for manufacturer. Example: Id=1052
9		000	
10		0000 0000	
11		0000 0100	
12	Time INTEGER (0..4294967295)	0100 0001	32 bit UNIX System Time, the number of seconds passed since 1st January 1970, 00:00 (UTC). Example: 1103790512 ₁₀
13		1100 1010	
14		1000 0001	
15		1011 0000	
16	Profile INTEGER (0..127,...)	0000 0000	Profile (p=0 ₁₀ : 1,5 MHz sub-carrier, p=1 ₁₀ : 2,0 MHz sub-carrier). Example: No extension, Profile 0
17	MandApplications SEQUENCE (0..127,..) OF {	0000 0001	No extension, Number of mandApplications= 1
18	OPTION indicator	0	EID not present
	OPTION indicator	0	Parameter not present
	AID_DSRCApplicationEntityID }	00 0001	No extension. AID = 1 ₁₀ =EFC
19	ProfileList SEQUENCE (0..127,..) OF Profile }	0000 0000	No extension, number of profiles in list = 0.
20	FCS	xxxx xxxx	Frame check sequence
21		xxxx xxxx	
22	FLAG	0111 1110	End Flag

2.2.1.2 Private window request

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	0110 0000	Private window request
7	FCS	xxxx xxxx	Frame check sequence
8		xxxx xxxx	
9	FLAG	0111 1110	End Flag

2.2.1.3 Private window allocation

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	0010 s000	Private window allocation
7	FCS	xxxx xxxx	Frame check sequence
8		xxxx xxxx	
9	FLAG	0111 1110	End Flag

2.2.1.4 Initialization response (VST)

Note: the present VST is an example of a VST containing only one application and EFC-ContextMark. VSTs with more EFC-ContextMarks (within the L2 frame length limit) shall also be correctly interpreted by the RSE.

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1100 0000	The frame contains a command LPDU
7	LLC control field	0000 0011	UI command
8	Fragmentation header	1xxx x001	No fragmentation. PDU # shall never be set to 0000 ₂ or 0001 ₂ .
9	VST SEQUENCE {	1001	INITIALISATION.response
	Fill BIT STRING (SIZE(4))	0000	Set to 0
10	Profile INTEGER (0..127,...)	0000 0000	No extension, profile p. Example : 0 ₁₀
11	Applications SEQUENCE (0..127,...) OF {	0000 0001	No extension, 1 application
12	OPTION indicator	1	EID present
	OPTION indicator	1	Parameter present
	AID DSRCApplicationEntityID	00 0001	No extension, AID = 1 (EFC)
13	EID	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
14	Parameter CONTAINER {	0000 0010	Choice 2 ₁₀ = Octet string
15		0000 0110	No extension, octet string length = 6 ₁₀
16	EFC-ContextMark SEQUENCE {		
	ContractProvider SEQUENCE {		
	CountryCode BIT STRING (SIZE(10))	0111 0100	As Specified in [EETS-OBE_data]
17		01	
	IssuerIdentifier INTEGER (0..16383) }	00 0000	As Specified in [EETS-OBE_data]
		0000 0001	
18	TypeOfContract OCTET STRING (SIZE(2))	0000 0011	Type of contract. As Specified in [EETS-OBE_data]
19		0000 0000	
20	ContextVersion INTEGER (0..127,...) }	0000 0001	No extension, context version. As Specified in [EETS-OBE_data]
A	CONTAINER {	0000 0010	No extension, Container Choice = 2 ₁₀ , Octet string
B	OCTET STRING	0000 0010	No extension, octet string length = 2 ₁₀
C	AC_CR-Reference SEQUENCE {		
	AC-MasterKeyRef Int1,	0000 0001	AC_CR-Reference to, consisting of AC_CR-MasterKeyRef and
D	AC_CR-Diversifier Int1 }	0000 0001	AC_CR.
E	CONTAINER {	0000 0010	No extension, Container Choice = 2 ₁₀ , Octet string
F		0000 0100	No extension, octet string length = 4 ₁₀
G	RndOBE Int4	0000 0000	Random Number (nonce) used together with AC_CRKey to
H		0000 0000	calculate AC_CR. Example : 640 ₁₀
I		0000 0010	
J	} } }	1000 0000	
22	ObeConfiguration SEQUENCE {		
	OPTION indicator	1	ObeStatus present
	EquipmentClass INTEGER (0..32767)	000 0000	Example : 3 ₁₀
23		0000 0011	
24	ManufacturerId INTEGER (0..65535)	0000 0000	Manufacturer identifier. See [AVI No] Register at
25		0000 0001	www.nen.nl/cen278 for value assignment. Kapsch = 1 ₁₀ .
26	ObeStatus INTEGER (0..65535)	0000 0011	Example : 768 ₁₀
27	} }	0000 0000	
28	FCS	xxxx xxxx	Frame check sequence
29		xxxx xxxx	
30	FLAG	0111 1110	End Flag

2.2.2 Presentation

2.2.2.1 Presentation request

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description	
1	FLAG	0111 1110	Start Flag	
2	Private LID	xxxx xxx0	Link address of a specific OBE	
3		xxxx xxx0		
4		xxxx xxx0		
5		xxxx xxx1		
6		MAC control field		1010 s000
7	LLC control field	n111 0111	Polled ACn command, n bit	
8	Fragmentation header	1xxx x001	No fragmentation. First service of chain.	
9	GET_STAMPED.request SEQUENCE {	0000 0101	ACTION.request (GET Stamped, AccessCredential not present, ActionParameter present, IID not present and Reply expected) or alternatively:	
		0000 1101	ACTION.request (GET Stamped, AccessCredentials, ActionParameter present, IID not present and Reply expected)	
10	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀	
11	ActionType INTEGER(0..127,...)	0000 0000	No extension, GET_STAMPED.request = 0	
A	AccessCredential OCTET STRING {	0000 0100	No extension, octet string length = 4 ₁₀	
B	AC_CR	0000 0100	Access credential calculated by RSE using RndOBE and the	
C		1001 0100		Access Credential Key AC_CRKey. Example: AC_CR(0) = 04 94 F8 97'H
D		1111 1000		
E		1001 0111		
12	ActionParameter CONTAINER {	0001 0001	No extension, Choice 17 ₁₀ = GetStampedRq	
13	AttributeldList SEQUENCE (0..127,...) OF {	0000 0001	No extension, number of attribute IDs = 1	
	INTEGER (0..127,...) Attributeld			
14	PaymentMeans }	0010 0000	Attributeld = 32 ₁₀ = PaymentMeans	
15	Nonce OCTET STRING {	0000 0100	No extension, octet string length = 4 ₁₀	
16	RndRSE	rrrr rrrr	Random number from RSE, containing SessionTime, needed to calculate the Authenticator	
17		rrrr rrrr		
18		rrrr rrrr		
19		rrrr rrrr		
20	KeyRef }	0110 1111	KeyRef_CI (e.g. =111 ₁₀)	
21	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as before (concatenation).	
22	GET.request SEQUENCE {	0110	GET.request	
	OPTION indicator	0	AccessCredential not present or alternatively:	
		1	AccessCredential present	
	OPTION indicator	0	IID not present	
	OPTION indicator	1	AttributeldList present	
	Fill BIT STRING(SIZE(1))	0	Set to 0	
23	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example : 5 ₁₀	
A	AccessCredential OCTET STRING {	0000 0100	No extension, octet string length = 4 ₁₀	
B	AC_CR	0000 0100	Access credential calculated by RSE using RndOBE and the	
C		1001 0100		Access Credential Key AC_CRKey. Example: AC_CR(0) = 04 94 F8 97'H
D		1111 1000		
E		1001 0111		
24	AttributeldList SEQUENCE (0..127,...) OF {			
	INTEGER (0..127,...) Attributeld {	0000 0110	No extension, number of attribute Ids = 6 ₁₀	
25	VehicleClass	0001 0001	Attributeld = 17 ₁₀ = VehicleClass	
26	VehicleAxles	0001 0011	Attributeld = 19 ₁₀ = VehicleAxles	
27	VehicleSpecificCharacteristics	0001 0110	Attributeld = 22 ₁₀ = VehicleSpecificCharacteristics	
28	EquipmentOBUID	0001 1000	Attributeld = 24 ₁₀ = EquipmentOBUID	
29	EquipmentStatus	0001 1010	Attributeld = 26 ₁₀ = EquipmentStatus	
30	ReceiptData1 }	0010 0001	Attributeld = 33 ₁₀ = ReceiptData1	
31	FCS	xxxx xxxx	Frame check sequence	
32		xxxx xxxx		
33	FLAG	0111 1110	End Flag	

2.2.2.2 Presentation response

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1101 0000	The frame contains a response LPDU
7	LLC control field	n111 0111	Response available, Acn command n bit
8	LLC status field	0000 0000	Response available and command accepted
9	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
10	GET_STAMPED.response SEQUENCE {	0001 0100	ACTION.response (Get Stamped rs)
11	EID INTEGER (0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
12	ResponseParameter CONTAINER {	0001 0010	No extension. Choice 18 ₁₀ = GetStampedRs
13	AttributeList SEQUENCE (0..127,...) OF {	0000 0001	No extension, number of attributes: 1
14	Attributes SEQUENCE { AttributeId	0010 0000	PaymentMeans = 32 ₁₀
15	AttributeValue CONTAINER {	0100 0000	Container Choice: 64 ₁₀ = PaymentMeans
16	PersonalAccountNumber	xxxx xxxx	PersonalAccountNumber
17		xxxx xxxx	
18		xxxx xxxx	
19		xxxx xxxx	
20		xxxx xxxx	
21		xxxx xxxx	
22		xxxx xxxx	
23		xxxx xxxx	
24		xxxx xxxx	
25		xxxx xxxx	
26	PaymentMeansExpiryDate	0001 1110	DateCompact. Example : 2005-03-01
27	PaymentMeansUsageControl }	0110 0001	Example : Not specified 0 ₁₀
28		0000 0000	
29	0000 0000		
30	Authenticator OCTET STRING {	0000 0100	No extension, octet string size = 4 ₁₀
31	Authenticator	xxxx xxxx	Authenticator over AttributeList (containing PaymentMeans) and RndRSE (containing SessionTime) calculated using AuKey
32		xxxx xxxx	
33		xxxx xxxx	
34		xxxx xxxx	
35	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
36	GET.response SEQUENCE	0111 0100	GET.response
37	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
38	AttributeList SEQUENCE (0..127,...) OF {	0000 0110	No extension, 6 attributes in list.
39	AttributeId INTEGER(0..127,...)	0001 0001	AttributeId = 17 ₁₀ = VehicleClass
40	Attribute Value CONTAINER {	0011 0001	Container choice = 49 ₁₀
41	VehicleClass }	1000 1001	VehicleClass Trailer present, CCC=000, class 3 (HV with 4 axles).
42	AttributeId INTEGER(0..127,...)	0001 0011	AttributeId = 19 ₁₀ = VehicleAxles
43	Attribute Value CONTAINER {	0011 0011	Container choice = 51 ₁₀
44	VehicleAxles	0000 0000	VehicleAxles value. Example: vehicle first axle height = not
45		0000 0011	specified, tyre type = not specified, 3 axles (without trailer).
46	AttributeId INTEGER(0..127,...)	0001 0110	AttributeId = 22 ₁₀ = VehicleSpecificCharacteristics
47	Attribute Value CONTAINER {	0011 0110	Container choice = 54 ₁₀
48	EnvironmentalCharacteristics(Euro type, Cop type)	0000	Example : no entry = 0
49	0000	0000	Example : no entry = 0
50	EngineCharacteristics	0000 0000	Example : no entry = 0
51	DescriptiveCharacteristics	0000 0000	Example : no entry = 0
52	FutureCharacteristics	0000 0000	Example : no entry = 0
53	AttributeId INTEGER(0..127,...)	0001 1000	AttributeId = 24 ₁₀ = EquipmentOBUId
54	Attribute Value CONTAINER {	0011 1000	Container choice = 56 ₁₀
55	Equipment OBU Id	0000 0100	OCTET STRING. Example: Kapsch's format (length indicator = 4, manufacturing year = 03, manufacturing month = 05, Serial number = 640)
56		0000 0011	
57		0000 0101	
58		0000 0010	
59	1000 0000		
59	AttributeId INTEGER(0..127,...)	0001 1010	AttributeId = 26 ₁₀ = EquipmentStatus
60	Attribute Value CONTAINER {	0011 1010	Container choice = 58 ₁₀
61	EquipmentStatus	0000 0000	EquipmentStatus (transaction counter). Example : Local use =
62		0011 1010	Not specified =0 ; transaction counter = 58.
63	AttributeId INTEGER(0..127,...)	0010 0001	AttributeId = 33 ₁₀ = ReceiptData1
64	Attribute Value CONTAINER {	0100 0001	Container choice = 65 ₁₀
65	ReceiptData1	0001 1010	ReceiptData1.SessionTime. Example : 2003-03-01, 21:12:10
66		0110 0001	
67		1010 1001	
68		1000 0101	
69	xxxx xxxx		ReceiptData1.SessionServiceProvider
70	xxxx xxxx		
71	xxxx xxxx		
72	xxxx xxxx		ReceiptData1.StationLocation
73	xxxx xxxx		

EETS-DSRC Transaction for Tolling and Enforcement

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
74		1000 0111	ReceiptData1.SessionLocation. Example: Ascending kilometrage and passage station type.
75		xxxx xxxx	ReceiptData1.SessionType
76		xxxx xxxx	ReceiptData1.SessionResult
77		xxxx xxxx	ReceiptData1.SessionTariffClass
78		xxxx xxxx	ReceiptData1.ClaimedClass
79		xxxx xxxx	ReceiptData1.SessionFee
80		xxxx xxxx	
81		xxxx xxxx	
82		xxxx xxxx	
83		1100 0000	ReceiptData1.SessionServiceProvider (from EFC-ContextMark).
84		0100 0000	Example: Austria, 1 ₁₀ , ASFINAG
85		0000 0001	
86		0000 0011	ReceiptData1.SessionType of contract (from EFC-ContextMark).
87		0000 0000	Example = 3 ₁₀
89		0000 0000	ReceiptData1.SessionContext version (from EFC-ContextMark).
90		xxxx xxxx	ReceiptData1.SessionAuthenticator
91		xxxx xxxx	
92		xxxx xxxx	
93		Xxxx xxxx	
94	FCS	Xxxx xxxx	Frame check sequence
95		xxxx xxxx	
96	FLAG	0111 1110	End Flag

2.2.3 Receipt

2.2.3.1 Set receipt request

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1010 s000	The frame contains a command LPDU
7	LLC control field	n111 0111	Polled ACn command, n bit
8	Fragmentation header	1xxx x001	No fragmentation. First service of chain.
9	GET_STAMPED.request SEQUENCE {	0000 0101 0000 1101	ACTION.request (GET Stamped, AccessCredential not present, ActionParameter present, IID not present and Reply expected) or alternatively: ACTION.request (GET Stamped, AccessCredentials, ActionParameter present, IID not present and Reply expected)
10	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example : 5 ₁₀
11	ActionType INTEGER(0..127,...)	0000 0000	No extension, GET_STAMPED.request = 0
A	AccessCredential OCTET STRING { AC_CR	0000 0100	No extension, octet string length = 4 ₁₀
B		0000 0100	Access credential calculated by RSE using RndOBE and the
C		1001 0100	Access Credential Key AC_CRKey. Example: AC_CR(0) =
D		1111 1000	04 94 F8 97'H
E		1001 0111	
12	ActionParameter CONTAINER {	0001 0001	No extension, Choice 17 ₁₀ = GetStampedRq
13	AttributeldList SEQUENCE (0..127,...) OF { INTEGER (0..127,...) Attributeld {	0000 0001	No extension, number of attribute IDs = 1
14	PaymentMeans } }	0010 0000	Attributeld = 32 ₁₀ = PaymentMeans
15	Nonce OCTET STRING {	0000 0100	No extension, octet string length = 4 ₁₀
16	RndRSE	rrrr rrrr	Random number from RSE, containing SessionTime, needed to calculate the Authenticator
17		rrrr rrrr	
18		rrrr rrrr	
19		rrrr rrrr	
20	KeyRef } }	0111 0110	KeyRef_OP (e.g. =118 ₁₀)
21	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as before (concatenation).
22	GET.request SEQUENCE {	OPTION indicator 0	AccessCredential not present or alternatively:
		OPTION indicator 1	AccessCredential present
		OPTION indicator 0	IID not present
		OPTION indicator 1	AttributeldList present
		Fill BIT STRING(SIZE(1)) 0	Set to 0
23	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
A	AccessCredential OCTET STRING { AC_CR	0000 0100	No extension, octet string length = 4 ₁₀
B		0000 0100	Access credential calculated by RSE using RndOBE and the
C		1001 0100	Access Credential Key AC_CRKey. Example: AC_CR(0) =
D		1111 1000	04 94 F8 97'H
E		1001 0111	
24	AttributeldList SEQUENCE (0..127,...) OF { INTEGER (0..127,...) Attributeld {	0000 0001	No extension, number of attribute lds = 1 ₁₀
25	VehicleLicencePlateNumber } }	0001 0000	Attributeld = 16 ₁₀ = VehicleLicencePlateNr
26	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as before (concatenation).
27	SET.request SEQUENCE {	OPTION indicator 0	SET.request (No AccessCredential, no IID, fill, reply expected) or alternatively:
		OPTION indicator 1	SET.request (AccessCredential, no IID, fill, reply expected)
28	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
A	AccessCredential OCTET STRING { AC_CR	0000 0100	No extension, octet string length = 4 ₁₀
B		0000 0100	Access credential calculated by RSE using RndOBE and the
C		1001 0100	Access Credential Key AC_CRKey. Example: AC_CR(0) =
D		1111 1000	04 94 F8 97'H
E		1001 0111	
29	AttributeList SEQUENCE ((0..127,...) OF { Attributes SEQUENCE {	0000 0011	No extension, number of attributes in list = 3 ₁₀
30	Attributeld INTEGER (0..127,...)	0001 1010	Attributeld = 26 ₁₀ = EquipmentStatus
31	Attribute Value CONTAINER {	0011 1010	Container choice = 58 ₁₀
32	EquipmentStatus	0000 0000	EquipmentStatus (transaction counter). Example : Local use =
33		0011 1011	Not specified =0 ; transaction counter = 59 (58 + 1).
34	Attributeld INTEGER(0..127,...)	0010 0001	Attributeld = 33 ₁₀ = ReceiptData1
35	Attribute Value CONTAINER {	0100 0001	Container choice = 65 ₁₀
36	ReceiptData1	xxxx xxxx	ReceiptData1.SessionTime
37		xxxx xxxx	
38		xxxx xxxx	
39		xxxx xxxx	
40		xxxx xxxx	

EETS-DSRC Transaction for Tolling and Enforcement

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
41		xxxx xxxx	
42		xxxx xxxx	
43		xxxx xxxx	ReceiptData1.StationLocation
44		xxxx xxxx	
45		xxxx xxxx	ReceiptData1.SessionLocation.
46		xxxx xxxx	ReceiptData1.SessionType
47		xxxx xxxx	ReceiptData1.SessionResult
48		xxxx xxxx	ReceiptData1.SessionTariffClass
49		xxxx xxxx	ReceiptData1.ClaimedClass
50		xxxx xxxx	ReceiptData1.SessionFee
51		xxxx xxxx	
52		xxxx xxxx	
53		xxxx xxxx	
54		xxxx xxxx	ReceiptData1.SessionContractProvider
55		xxxx xxxx	
56		xxxx xxxx	
57		xxxx xxxx	ReceiptData1.SessionTypeOfContract
58		xxxx xxxx	
59		xxxx xxxx	ReceiptData1.SessionContextVersion
60		xxxx xxxx	ReceiptData1.Authenticator
61		xxxx xxxx	
62		xxxx xxxx	
63		xxxx xxxx	
64	Attributeld INTEGER (0..127,...)	0010 0010	Attributeld = 34 ₁₀ = ReceiptData2
65	Attribute Value CONTAINER {	0100 0010	Container choice = 66 ₁₀
66	ReceiptData2	xxxx xxxx	ReceiptData2. Same format as ReceiptData1
...		
93		xxxx xxxx	
94	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as before (concatenation).
95	SET_MMI.request SEQUENCE {	0000 0101	ACTION.request (no AccCred, ActionPar, no IID, confirmed, reply)
96	EID INTEGER(0..127,...)	0000 0000	No extension, EID = 0 (system element)
97	ActionType INTEGER(0..127,...)	0000 1010	No extension, SET_MMI.request = 10 ₁₀
98	ActionParameter CONTAINER	xxxx xxxx	No extension, Use Type 69 (preferred) or Type 0 depending on setting in TSP list at RSE
99	SetMMI INTEGER }	0000 0000	Example : ok (0 ₁₀)
100	FCS	xxxx xxxx	Frame check sequence
101		xxxx xxxx	
102	FLAG	0111 1110	End Flag

2.2.3.2 Set receipt response

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1101 0000	The frame contains a response LPDU
7	LLC control field	n111 0111	Acn command n bit
8	LLC status field	0000 0000	Response available and command accepted
9	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
10	GET_STAMPED.response SEQUENCE {	0001 0100	ACTION.response (Get Stamped rs)
11	EID INTEGER (0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
12	ResponseParameter CONTAINER {	0001 0010	No extension. Choice 18 ₁₀ = GetStampedRs
13	AttributeList SEQUENCE (0..127,...) OF {	0000 0001	No extension, number of attributes: 1
14	Attributes SEQUENCE { AttributeId	0010 0000	PaymentMeans = 32 ₁₀
15	AttributeValue CONTAINER {	0100 0000	Container Choice: 64 ₁₀ = PaymentMeans
16	PersonalAccountNumber	xxxx xxxx	PersonalAccountNumber
17		xxxx xxxx	
18		xxxx xxxx	
19		xxxx xxxx	
20		xxxx xxxx	
21		xxxx xxxx	
22		xxxx xxxx	
23		xxxx xxxx	
24		xxxx xxxx	
25		xxxx xxxx	
26	PaymentMeansExpiryDate	0001 1110	DateCompact. Example : 2005-03-01
27	PaymentMeansUsageControl	0110 0001	Example : Not specified 0 ₁₀
28		0000 0000	
29	}	0000 0000	
30	Authenticator OCTET STRING {	0000 0100	No extension, octet string size = 4 ₁₀
31	Authenticator	xxxx xxxx	Authenticator over AttributeList (containing PaymentMeans) and RndRSE (containing SessionTime) calculated using AuKey
32		xxxx xxxx	
33		xxxx xxxx	
34		xxxx xxxx	
35	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
36	GET.response SEQUENCE	0111 0100	GET.response
37	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
38	AttributeList SEQUENCE (0..127,...) OF {	0000 0001	No extension, 1 attributes in list.
39	AttributeId INTEGER (0..127,...)	0001 0000	AttributeId = 16 ₁₀ = VehicleLicencePlateNo
40	Attribute Value CONTAINER {	0010 1111	Container choice = 47 ₁₀
41	Vehlpn {SEQUENCE countryCode, AlphabetIndicator, LicencePlateNumber	1010 0100	VehicleLicencePlateNumber. Example : Country: SE, 00 00 0000 0000 1010 0100 1111 0100 0011 0100 0100 0011 0101 0011 0110 0011 0000 0000 0000 0000 0000 0000 0000 0000 0000
42		00	
43		00 0000	
44		0000 1010	
45		0100 1111	
46		0100 0011	
47		0100 0100	
48		0011 0101	
49		0011 0110	
50		0011 0000	
51		0000 0000	
52		0000 0000	
53		}	
54	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
55	SET.response SEQUENCE {	0101	SET.response
	OPTION indicator	0	IID not present
	OPTION indicator	0	ReturnStatus not present
	Fill BIT STRING (SIZE(2))	00	Set to 0
56	EID INTEGER (0..127,...) }	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
57	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
58	ACTION.response SEQUENCE {	0001	SET_MMI.response
	OPTION indicator	0	IID not present
	OPTION indicator	0	ResponseParameter not present
	OPTION indicator	0	ReturnStatus not present
	Fill BIT STRING (SIZE(1))	0	Set to 0
59	EID INTEGER (0..127,...) }	0000 0000	No extension, System Element EID = 0
60	FCS	xxxx xxxx	Frame check sequence
61		xxxx xxxx	
62	FLAG	0111 1110	End Flag

2.2.4 Tracking and closing

2.2.4.1 Tracking request (Echo.request)

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1010 s000	The frame contains a command LPDU
7	LLC control field	n111 0111	Polled ACn command n bit
8	Fragmentation header	1xxx x001	No fragmentation.
9	ECHO.request SEQUENCE {	0000	ACTION.request
	OPTION indicator	0	No Access Credentials
	OPTION indicator	1	ActionParameter present
	OPTION indicator	0	IID not present
	Mode BOOLEAN	1	Reply expected
10	EID INTEGER (0..127,...)	0000 0000	No extension, EID = 0
11	ActionType INTEGER (0..127,...)	0000 1111	No extension, ECHO.request = 15
12	ActionParameter CONTAINER	0000 0010	No extension, Choice 2 ₁₀ = Octet string
13	}	0000 0000	No extension. String length = 0 octets
14	FCS	xxxx xxxx	Frame check sequence
15		xxxx xxxx	
16		xxxx xxxx	
16	FLAG	0111 1110	End Flag

2.2.4.2 Tracking response (Echo.response)

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1101 0000	The frame contains a response LPDU
7	LLC control field	n111 0111	ACn command n bit
8	LLC status field	0000 0000	Response available and command accepted
9	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
10	ECHO.response SEQUENCE {	0000	ACTION.response
	OPTION indicator	0	No IID
	OPTION indicator	1	ResponseParameter present
	OPTION indicator	0	ResponseStatus not present
	FILL BIT STRING (SIZE(1))	1	Set to 0.
11	EID INTEGER (0..127,...)	0000 0000	No extension, EID = 0
12	ResponseParameter CONTAINER	0000 0010	No extension, Choice 2 ₁₀ = Octet string
13	}	0000 0000	No extension. String length = 0 octets
14	FCS	xxxx xxxx	Frame check sequence
15		xxxx xxxx	
16		xxxx xxxx	
16	FLAG	0111 1110	End Flag

2.2.4.3 Closing

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1000 0000	The frame contains a command LPDU
7	LLC control field	0000 0011	UI command
8	Fragmentation header	1xxx x001	No fragmentation.
9	RELEASE.request SEQUENCE {	0010	EVENT_REPORT.request
	OPTION indicator	0	AccessCredential not present
	OPTION indicator	0	EventParameter not present
	OPTION indicator	0	IID not present
	Mode BOOLEAN	0	No reply expected
10	EID INTEGER (0..127,...)	0000 0000	No extension, EID = 0 (system element)
11	EventType INTEGER (0..127,...) }	0000 0000	No extension, RELEASE = 0.
12	FCS	xxxx xxxx	Frame check sequence
13		xxxx xxxx	
14	FLAG	0111 1110	End Flag

3 EETS Enforcement only transaction

The EETS enforcement only transaction will be used by dedicated enforcement equipment where no tolling functionality is needed, e.g. at mobile enforcement equipment. In contrast to the combined “tolling and enforcement transaction”, only a subset of attributes and the receipt data are read.

3.1 Bit-level specification

3.1.1 Initialization

The Initialisation phase is the same as for the EETS Tolling and Enforcement Transaction, see chapter 0.

3.1.2 Presentation 1

Similar to the Presentation Phase for the EETS Tolling and Enforcement Transaction, but only a subset of data is read-out.

3.1.2.1 Presentation 1 request

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6		MAC control field	
7	LLC control field	n111 0111	Polled ACn command, n bit
8	Fragmentation header	1xxx x001	No fragmentation. First service of chain.
9	GET_request SEQUENCE {	0110	GET_request
	OPTION indicator	0	AccessCredential not present or alternatively: AccessCredential present
	OPTION indicator	0	IID not present
	OPTION indicator	1	AttributeIdList present
	Fill BIT STRING(SIZE(1))	0	Set to 0
10	EID INTEGER(0..127,...)	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
A	AccessCredential OCTET STRING { AC_CR	0000 0100	No extension, octet string length = 4 ₁₀
B		0000 0100	Access credential calculated by RSE using RndOBE and the
C		1001 0100	Access Credential Key AC_CRKey. Example: AC_CR(0) =
D		1111 1000	04 94 F8 97'H
E		1001 0111	
11	AttributeIdList SEQUENCE (0..127,...) OF {		
	INTEGER (0..127,...) AttributeId {	0000 0110	No extension, number of attribute Ids = 6 ₁₀
12	VehicleLicencePlateNumber	0001 0000	AttributeId = 16 ₁₀ = VehicleLicencePlateNr
13	VehicleClass	0001 0001	AttributeId = 17 ₁₀ = VehicleClass
14	VehicleAxles	0001 0011	AttributeId = 19 ₁₀ = VehicleAxles
15	VehicleSpecificCharacteristics	0001 0110	AttributeId = 22 ₁₀ = VehicleSpecificCharacteristics
16	EquipmentOBUId	0001 1000	AttributeId = 24 ₁₀ = EquipmentOBUId
17	EquipmentStatus } } }	0001 1010	AttributeId = 26 ₁₀ = EquipmentStatus
18	FCS	xxxx xxxx	Frame check sequence
19		xxxx xxxx	
20	FLAG	0111 1110	End Flag

3.1.2.2 Presentation 1 response

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1101 0000	The frame contains a response LPDU
7	LLC control field	n111 0111	Response available, Acn command n bit
8	LLC status field	0000 0000	Response available and command accepted
9	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
10	GET.response	SEQUENCE 0111 0100	GET.response
11	EID	INTEGER(0..127,...) 0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
12	AttributeList	SEQUENCE (0..127,...) OF { 0000 0111	No extension, 7 attributes in list.
13	Attributeld	INTEGER(0..127,...) 0001 0000	Attributeld = 16 ₁₀ = VehicleLicencePlateNo
14	Attribute Value	CONTAINER { 0010 1111	Container choice = 47 ₁₀
15	Vehlpn { AlphabetIndicator, LicencePlateNumber	SEQUENCE countryCode, 1010 0100	VehicleLicencePlateNumber. Example : Country: SE,
16		00	00
17		00 0000	alphabet indicator no 1
18		0000 1010	length indicator = 10 ₁₀ chars
19		0100 1111	OCD560, padded with 4 'NUL'-characters
20		0100 0011	
21		0100 0100	
22		0011 0101	
23		0011 0110	
24		0011 0000	
25		0000 0000	
26	0000 0000		
27	}	0000 0000	
28	Attributeld	INTEGER(0..127,...) 0001 0001	Attributeld = 17 ₁₀ = VehicleClass
29	Attribute Value	CONTAINER { 0011 0001	Container choice = 49 ₁₀
30	VehicleClass	1000 1001	VehicleClass Trailer present, CCC=000, class 3 (HV with 4 axles).
31	Attributeld	INTEGER (0..127,...) 0001 0011	Attributeld = 19 ₁₀ = VehicleAxles
32	Attribute Value	CONTAINER { 0011 0011	Container choice = 51 ₁₀
33	VehicleAxles	0000 0000	VehicleAxles value. Example: vehicle first axle height = not
34		0000 0011	specified, tyre type = not specified, 3 axles (without trailer).
35	Attributeld	INTEGER (0..127,...) 0001 0110	Attributeld = 22 ₁₀ = VehicleSpecificCharacteristics
36	Attribute Value	CONTAINER { 0011 0110	Container choice = 54 ₁₀
37	EnvironmentalCharacteristics (Euro type, Cop type)	0000	Example : no entry = 0
38	EngineCharacteristics	0000 0000	Example : no entry = 0
39	DescriptiveCharacteristics	0000 0000	Example : no entry = 0
40	FutureCharacteristics	0000 0000	Example : no entry = 0
41	Attributeld	INTEGER (0..127,...) 0001 1000	Attributeld = 24 ₁₀ = EquipmentOBUId
42	Attribute Value	CONTAINER { 0011 1000	Container choice = 56 ₁₀
43	Equipment OBU Id	0000 0100	OCTET STRING. Example: Kapsch's format (length indicator = 4, manufacturing year = 03, manufacturing month = 05, Serial number = 640)
44		0000 0011	
45		0000 0101	
46		0000 0010	
47		1000 0000	
48	Attributeld	INTEGER(0..127,...) 0001 1010	Attributeld = 26 ₁₀ = EquipmentStatus
49	Attribute Value	CONTAINER { 0011 1010	Container choice = 58 ₁₀
50	EquipmentStatus	0000 0000	EquipmentStatus (transaction counter). Example : Local use =
51		0011 1010	Not specified =0 ; transaction counter = 58.
52	FCS	Xxxx xxxx	Frame check sequence
53		xxxx xxxx	
54	FLAG	0111 1110	End Flag

3.1.3 Presentation 2

Similar to the Presentation Phase for the EETS Tolling and Enforcement Transaction, but only receipts are read-out.

3.1.3.1 Presentation 2 request

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1010 s000	The frame contains a command LPDU
7	LLC control field	n111 0111	Polled ACn command, n bit
8	Fragmentation header	1xxx x001	No fragmentation. First service of chain.
9	GET.request	0110	GET.request
	OPTION indicator	0	AccessCredential not present or alternatively: AccessCredential present
	OPTION indicator	0	IID not present
	OPTION indicator	1	AttributeldList present
	Fill	0	Set to 0
10	EID	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
A	AccessCredential	0000 0100	No extension, octet string length = 4 ₁₀
B	AC_CR	0000 0100	Access credential calculated by RSE using RndOBE and the
C		1001 0100	Access Credential Key AC_CRKey. Example: AC_CR(0) =
D		1111 1000	04 94 F8 97'H
E		1001 0111	
		AttributeldList	
11	AttributeldList	SEQUENCE (0..127,...) OF {	
	INTEGER (0..127,...)	Attributeld {	No extension, number of attribute lds = 2 ₁₀
	ReceiptData1	0010 0001	Attributeld = 33 ₁₀ = ReceiptData1
	ReceiptData2	0010 0010	Attributeld = 34 ₁₀ = ReceiptData1
14	FCS	xxxx xxxx	Frame check sequence
15		xxxx xxxx	
16	FLAG	0111 1110	End Flag

3.1.3.2 Presentation 2 response

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
1	FLAG	0111 1110	Start Flag
2	Private LID	xxxx xxx0	Link address of a specific OBE
3		xxxx xxx0	
4		xxxx xxx0	
5		xxxx xxx1	
6	MAC control field	1101 0000	The frame contains a response LPDU
7	LLC control field	n111 0111	Response available, Acn command n bit
8	LLC status field	0000 0000	Response available and command accepted
9	Fragmentation header	1xxx x001	No fragmentation. Same PDU # as in the corresponding request.
10	GET.response	0111 0100	GET.response
11	EID	0000 0101	Uniquely associated with a context mark in the OBE. Example 5 ₁₀
12	AttributeldList	SEQUENCE (0..127,...) OF {	No extension, 2 attributes in list.
	Attributeld	0010 0001	Attributeld = 33 ₁₀ = ReceiptData1
	Attribute Value	CONTAINER {	Container choice = 65 ₁₀
	ReceiptData1	0001 1010	ReceiptData1.SessionTime. Example : 2003-03-01, 21:12:10
16		0110 0001	
17		1010 1001	
18		1000 0101	
19	xxxx xxxx		ReceiptData1.SessionServiceProvider
20	xxxx xxxx		ReceiptData1.StationLocation
21	xxxx xxxx		
22	xxxx xxxx		
24		1000 0111	ReceiptData1.SessionLocation. Example: Ascending kilometrage and passage station type.
25		xxxx xxxx	ReceiptData1.SessionType
26		xxxx xxxx	ReceiptData1.SessionResult

Octet #	Attribute / Field	Bits in Octet b ₇ b ₀	Description
27		xxxx xxxx	ReceiptData1.SessionTariffClass
28		xxxx xxxx	ReceiptData1.ClaimedClass
29		xxxx xxxx	ReceiptData1.SessionFee
30		xxxx xxxx	
31		xxxx xxxx	
32		xxxx xxxx	
33		1100 0000	ReceiptData1.SessionServiceProvider. Example: Austria, 1 ₁₀ (ASFINAG)
34		0100 0000	
35		0000 0001	Type of contract. Example : HVG post paid contract = 3 ₁₀
36		0000 0011	
37		0000 0000	Security key version 0,version 1.0 of the Austrian HGV transaction
38		0000 0000	
39		xxxx xxxx	ReceiptData1.Authenticator
40		xxxx xxxx	
41		xxxx xxxx	
42		Xxxx xxxx	
43	Attributeld INTEGER (0..127,...)	0010 0010	Attributeld = 34 ₁₀ = ReceiptData2
44	Attribute Value CONTAINER {	0100 0010	Container choice = 66 ₁₀
45	ReceiptData2	xxxx xxxx	ReceiptData2. Same format as ReceiptData1
....		
72	}	xxxx xxxx	
73	FCS	xxxx xxxx	
74		xxxx xxxx	
75	FLAG	0111 1110	End Flag

3.1.4 Closing

The closing phase is the same as for the EETS Tolling and Enforcement Transaction, see chapter 0.

4 Annex A - References

Reference	Document Ref	Date / Version	Document title
[EETS-DSRC]			EETS-DSRC Transaction for Tolling and Enforcement (this document)
[EETS-OBE_data]			EETS-OBE Personalization, Configuration and Operation Data Description
[IAP]	EN 15509	2007	EN 15509:2007 Road Traffic and Transport Telematics (RTTT) – Electronic Fee Collection – Interoperability application profile for DSRC
[EFC API]	EN ISO 14906	2011	Road Traffic and Transport Telematics (RTTT) – Electronic Fee Collection – Application interface definition for dedicated short range communication
[GSS]	GSS	V3.2:2003	Global Specification for Short Range Communication (Kapsch TrafficCom AB, Kapsch Telecom GmbH, Thales e-Transactions CGA SA, version 3.2, 2003-08, http://www.etc-interop.com/pdf/gss_32.pdf)
[L1]	EN 12253	2004	Road Transport and Traffic Telematics (RTTT) – Dedicated Short-Range Communication (DSRC) – Physical layer using microwave at 5.8 GHz
[L2]	EN 12795	2003	Road Transport and Traffic Telematics (RTTT) – Dedicated Short-Range Communication (DSRC) – DSRC data link layer: Medium access and logical link control
[L7]	EN 12834 (ISO 15628)	2003	Road Transport and Traffic Telematics (RTTT) – Dedicated Short-Range Communication (DSRC) – Application Layer
[Profiles]	EN 13372	2004	Road Transport and Traffic Telematics (RTTT) – Dedicated Short-Range Communication (DSRC) – Profiles for RTTT applications
[AVI No]	EN ISO 14816	2005	Road Traffic and Transport Telematics (RTTT) – Automatic Vehicle and Equipment Identification – Numbering and Data Structures

